

DataSheet

This demineralised water fire extinguisher is for use on Class A fires – those involving flammable solids, including paper, wood and textiles. A wholly waterbased fire extinguisher, however, comes with a strict warning that it shouldn't be used on electrical fires. That's because water can act as a conductor of electricity and so it's extremely dangerous. A water fire extinguisher should never be used on Class B (involving flammable liquids), Class C (flammable gases) or Class F (cooking oil and grease) fires either.



WATER FIRE EXTINGUISHERS

Water fire extinguishers work by having a cooling effect, lowering the temperature of the fire when sprayed on it. Hospitals, schools and offices would benefit from having a water extinguisher on site as well as warehouses and storage units.

Technical Specification	WS6E
Capacity	6 litre
Fire Rating	13A
Extinguishing Medium	Demineralised water
Working Pressure	15 bar at temp 20°C
Temperature Range	+5-+60°C
Cylinder Material	Steel
Pressuring Gas	Nitrogen

C@MMANDEREDGE

PRODUCT CODE WS6E

PRODUCT GROUP CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter) 502 x 197 x 160

WEIGHT 9.3kg

- Fully CE marked
- Plastic base for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Manufactured in Europe



sales@checkfire.co.uk

029 2085 0627

www.CheckFire.co.uk



CheckFire Ltd., Sir Alfred Owen Way, Pontygwindy Industrial Estate, Caerphilly CF83 3HU